PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C.20231
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 29 May 2000 (29.05.00)	
International application No. PCT/SE99/01798	**Applicant's or agent's file reference** 2008127
International filing date (day/month/year) 07 October 1999 (07.10.99)	**Priority date** (day/month/year) 07 October 1998 (07.10.98)

Applicant

LINDGREN, Per et al

---

1. The designated Office is hereby notified of its election made:

   [X] in the demand filed with the International Preliminary Examining Authority on:

   18 April 2000 (18.04.00)

   [ ] in a notice effecting later election filed with the International Bureau on:

2. The election [X] was

   [ ] was not

   made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	**Authorized officer** A. Karkachi
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF THE RECORDING OF A CHANGE

(PCT Rule 92bis.1 and
Administrative Instructions, Section 422)

From the INTERNATIONAL BUREAU

To:

AWAPATENT AB
P.O. Box 45086
S-104 30 Stockholm
SUÈDE

Date of mailing (day/month/year) 29 May 2000 (29.05.00)	
Applicant's or agent's file reference 2008127	**IMPORTANT NOTIFICATION**
International application No. PCT/SE99/01798	**International filing date** (day/month/year) 07 October 1999 (07.10.99)

1. The following indications appeared on record concerning:

[X] the applicant   [X] the inventor   [ ] the agent   [ ] the common representative

Name and Address BOHM, Christer Varpholmsgränd 32 S-127 46 Skärholmen Sweden	State of Nationality SE	State of Residence SE
	Telephone No.	
	Facsimile No.	
	Teleprinter No.	

2. The International Bureau hereby notifies the applicant that the following change has been recorded concerning:

[ ] the person   [ ] the name   [X] the address   [ ] the nationality   [ ] the residence

Name and Address BOHM, Christer Skurusundsvägen 40 S-131 46 Nacka Sweden	State of Nationality SE	State of Residence SE
	Telephone No.	
	Facsimile No.	
	Teleprinter No.	

3. Further observations, if necessary:

4. A copy of this notification has been sent to:

[X] the receiving Office   [ ] the designated Offices concerned

[ ] the International Searching Authority   [X] the elected Offices concerned

[X] the International Preliminary Examining Authority   [ ] other:

The International Bureau of WIPO **34, chemin des Colombettes** **1211 Geneva 20, Switzerland**	Authorized officer A. Karkachi
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38

Form PCT/IB/306 (March 1994)   003316382

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

REC'D 0 2 MAR 2001
WIPO PCT

14

Applicant's or agent's file reference PC_2008127	FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)
International application No. PCT/SE99/01798	International filing date *(day month year)* 07.10.1999	Priority date *(day month year)* 07.10.1998

International Patent Classification (IPC) or national classification and IPC7

H04L 12/52, H04L 12/56, H04Q 11/04

Applicant

NET INSIGHT AB et al.

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of   5   sheets, including this cover sheet.

   ☐ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

   These annexes consist of a total of _____ sheets.

3. This report contains indications relating to the following items:

   I   ☒ Basis of the report

   II ☐ Priority

   III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

   IV ☐ Lack of unity of invention

   V   ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

   VI ☐ Certain documents cited

   VII ☐ Certain defects in the international application

   VIII ☐ Certain observations on the international application

Date of submission of the demand 18.04.2000	Date of completion of this report 23.02.2001
Name and mailing address of the IPEA/SE Patent- och registreringsverket Telex: Box 5055 17979 S-102 42 STOCKHOLM PATOREG-S Facsimile No. 08-667 72 88	Authorized officer Rickard Elg/LR Telephone No. 08-782 25 00

Form PCT/IPEA/409 (cover sheet) (January 1998)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE99/01798

I. Basis of the report

1. With regard to the **elements** of the international application:*

   ☒ the international application as originally filed

   ☐ the description:
   pages _____ , as originally filed
   pages _____ , filed with the demand
   pages _____ , filed with the letter of _____

   ☐ the claims:
   pages _____ , as originally filed
   pages _____ , as amended (together with any statement) under article 19
   pages _____ , filed with the demand
   pages _____ , filed with the letter of _____

   ☐ the drawings:
   pages _____ , as originally filed
   pages _____ , filed with the demand
   pages _____ , filed with the letter of _____

   ☐ the sequence listing part of the description:
   pages _____ , as originally filed
   pages _____ , filed with the demand
   pages _____ , filed with the letter of _____

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.
   These elements were available or furnished to this Authority in the following language _____ which is:

   ☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).

   ☐ the language of publication of the international application (under Rule 48.3(b)).

   ☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/ or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

   ☐ contained in the international application in written form.

   ☐ filed together with the international application in computer readable form.

   ☐ furnished subsequently to this Authority in written form.

   ☐ furnished subsequently to this Authority in computer readable form.

   ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

   ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. ☐ The amendments have resulted in the cancellation of:

   ☐ the description, pages _____

   ☐ the claims, Nos. _____

   ☐ the drawings, sheet/fig _____

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2 (c)).**

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

** Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.

V.	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Claims	1-16	YES
	Claims		NO
Inventive step (IS)	Claims	1-16	YES
	Claims		NO
Industrial applicability (IA)	Claims	1-16	YES
	Claims		NO

2. Citations and explanations (Rule 70.7)

The invention relates to an apparatus for providing routing of asynchronous traffic in a circuit-switched synchronous time division multiplexed network.

When transferring asynchronous traffic through a circuit-switched synchronous time division multiplexed network, a routing mechanism is needed. The routing mechanism is typically provisioned by routing apparatuses at different locations in the network, where said routing apparatuses comprise one or many interfaces proving access to respective multi-channel bitstreams carrying isochronous channels, a routing processor for providing routing of data packets and a communication bus interconnecting said interfaces and said routing processor. When several interfaces needs to access the routing processor, the capacity demand placed upon routing processor and the transfer capacity demand placed upon the communication bus becomes high. Since shortage of capacity could introduce delay and, if severe, perhaps even cause loss of data, there is problem to be solved.

The invention alleviates this problem by limiting the amount of data transferred on the communication medium, by transmitting only the header portion of each data packet from the interface to the routing processor, while at least the remaining part of the data packets is stored at said interface. Consequently, this also limits the amount of data handled by the routing processor.

The following documents have been cited in the International Search Report:

.../...

Supplemental Box
(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: V

D1: WO, 9501031, A1
D2: WO, 9703526, A2
D3: WO, 9417617, A1
D4: EP, 0537743, A1
D5: C. Bohm et al., "The DTM Gigabit Network", Journal of High Speed Networks, vol. 3, 1994, pp. 109-126

Document D1 discloses a method for avoiding conflicts in a switch core, thereby eliminating the need for cell buffers in the core. Cells are directed through the core by means of tags. A tag is a routing information preceding each cell. Tagging is carried through in the ports. Each tag contains routing information which is not related to the immediately arriving cell, but to some cell following thereafter, thus the cells are delayed in the ports. Processing of the routing information is carried through in the core, after which scheduling information is fed back to the ports.

Document D2 discloses a telecommunications facility for transporting data packets having headers and payloads between a plurality of input ports and a plurality of output ports. A concentrator for multiplexing payloads into an incoming data stream and headers into an incoming header stream is provided. A memory controller, responsive to information contained in the headers in the incoming header stream, generates queue control information for relating each data packet to one of a plurality of output ports and generates headers in the outgoing header stream for packets destined for any of the output ports as well as scheduling information. A distributor directs outgoing headers from an outgoing header stream along with respective payloads from an outgoing payload stream to those of the output ports to which the data packets are destined. A buffer, responsive to the incoming data stream and to the queue control information, queues the payload of each related data packet into a queue associated with the output port to which the payload is destined. The buffer also selects and transfers the queued payload data units of each data packet into an intermediate data stream. A time slot switch receives a frame of payloads from the intermediate data stream and reorders data units from selected payloads into a switched data stream, in response to time slot switching information, The time slot switch also multiplexes reordered data units of a preceding frame of payloads from the switched data stream with the un-selected payloads of data from the intermediate data stream into the outgoing data stream, in response to the scheduling information from the memory controller.   .../...

Form PCT/IPEA/409 (Supplemental Box) (January 1998)

Supplemental Box
(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: suppl.1

Document D3 discloses an ATM switch, which may be modified to provide a predetermined delay when transmitting information cells, thereby enabling isochronous traffic.

Document D4 discloses a method for increasing switching speed. Header and payload portions of arriving cells are separated. Header conversion operation is performed in respect of the header and the payload portion is written to a common memory.

Document D5 discloses a circuit-switched synchronous time division multiplexed network architecture called DTM.

According to the aforementioned, D1, D2 and D4, discloses various methods for limiting the amount of data handled by switch core, by separating headers from the remaining portion of data packets. Consequently, the idea of separating headers from the remaining portions of a data packet for reducing the amount of data to be processed is known. However, the methods revealed by documents D1, D2 and D3 concerns circuit-switched asynchronous networks and the problem associated with capacity shortage when routing asynchronous traffic over a circuit-switched synchronous time division multiplexed network is not discussed. In fact it appears that none of documents D1-D5, neither explicit nor implicit, addresses this problem. Therefore, it is not considered obvious to a person skilled in the art arriving at invention from any one, or any combination of documents D1-D5. Consequently, the invention claimed in claims 1-16 is considered to involve an inventive step.

The invention claimed in claims 1-16 is novel and shows industrial applicability

APPARATUS FOR ROUTING ASYNCHRONOUS TRAFFIC IN A CIRCUIT SWITCHED NETWORK

Technical Field of Invention

The present invention refers to an apparatus providing routing of asynchronous traffic in a circuit switched synchronous time division multiplexed network,
5   said apparatus comprising: an interface providing access to a multi-channel bitstream carrying isochronous channels; routing means for providing routing of data packets; and a communication medium interconnecting said interface and said routing means.
10

Background of the invention

Today, new types of circuit-switched communication networks are being developed for the transfer of information using synchronous time division multiplexed bit-
15   streams. Within this field, a new technology, referred DTM (Dynamic synchronous Transfer Mode), are currently being developed, primarily addressing the problem of providing quality of service to users of real-time, broadband applications.
20   The structure of a DTM network has been described in, e.g., "The DTM Gigabit Network", Christer Bohm, Per Lindgren, Lars Ramfelt, and Peter Sjödin, Journal of High Speed Networks, 3(2):109-126, 1994, and in "Multi-gigabit networking based on DTM", Lars Gauffin, Lars Håkansson,
25   and Björn Pehrson, Computer networks and ISDN Systems, 24(2):119-139, April 1992.

The basic topology of a DTM network is preferably a bus with two unidirectional, multi-access, multi-channel optical fibers connecting a number of nodes, each node
30   being arranged to serve one or more end users connected thereto. However, the topology may just as well be any other kind of structures e.g. a ring structure or a hub structure.

When transferring asynchronous traffic, such as TCP/IP packets or Ethernet frames, a mechanism for providing routing of such traffic through, e.g., a DTM network is needed. This is typically solved by the
5   provision of routing apparatuses at different locations in the network.

Typically, such a routing apparatus comprises one or more interfaces providing access to respective multi-channel bitstreams carrying isochronous channels, a
10   routing processor for providing routing of data packets, and a communication bus interconnecting said interfaces and said routing processor.

A problem in this type of routing apparatus is that the capacity demand placed upon on the routing processor,
15   as well as the transfer capacity demand placed upon the communication bus, becomes high as several interfaces needs access to the function provided by the one routing processor. When these demands exceed the available capa-city, blocking will occur, resulting in delays or even
20   loss of data.

An object of the invention is therefore to provide a routing apparatus designed to reduce the risk of lack of capacity, thereby limiting the occurrence of blocking or loss of data in relation to the routing processor.
25

Summary of the invention

The above mentioned and other objects of the invention are achieved by the invention as defined in the accompanying claims.
30   According to an aspect of the invention, there is provided and apparatus of the kind mentioned in the introduction, wherein said interface comprises means for deriving data packets received in at least one of said isochronous channels, means for transmitting only header
35   portions of said data packets to said routing means via said communication medium, means for temporarily storing at least body portions of said data packets, and means

for forwarding said data packets in accordance with
routing instructions received from said routing means.

The invention is thus based upon the idea of limi-
ting the amount of data transferred on said communication

5   medium, and consequently handled by the routing proces-
sor, by only transmitting the header portion of each data
packet from said interface to said routing processor,
while storing the data packet, or at least the remaining
part of the data packet, at said interface. Thus, the

10   communication medium and the routing processor do not
have to handle the entire data packet, but merely a small
portion thereof. Typically, in many applications the only
portion of the data packet that actually has to be trans-
mitted to the routing processor will be the destination

15   address of the data packet, even though the invention is
not limited thereto.

An advantage of the invention is that a lesser
amount of data is transmitted over said communication
medium, which typically is a processor bus, thereby

20   reducing the risk of transfer capacity shortage at the
communication bus. Another advantage of the invention is
that the routing processor is not required to store an
entire data packet, but merely needs to handle a header
portion thereof. Furthermore, if the step of deriving or

25   extracting the destination address, or other desired
information, from the data packet is performed at said
interface, the routing processor is relieved from the
burden of extracting such information, thereby further
reducing the need for processing capacity at the routing

30   processor.

Event though the invention provides a significant
advantage with reference to the situation wherein one
interface is connected to the routing processor, the
advantage is of course magnified in a situation wherein

35   several interfaces are connected to access one or more
routing processor.

According to a preferred embodiment of the inven-
tion, said interface comprises selecting means for deter-
mining if a header portion of a data packet is to be sent
to said routing means, and wherein said means for trans-
5   mitting only header portions of said data packets to said
routing means are arranged to control the transmission of
header portions according to decision made by said selec-
ting means. Preferably, said selecting means comprises a
table designating destination addresses of data packets
10   for which the header portions thereof are not to be
transmitted to said routing means.

Typically, in such an embodiment, only header
portions of data packets that actually require routing by
the routing processor are transmitted over the communica-
15   tion medium to the routing processor. However, header
portions of data packets that are to be discarded at said
interface (i.e. that are not to be routed at all), that
are to be transmitted using another channel accessed by
said interface, and/or that are to by bypassed (i.e.
20   transmitted in the same channel as they were received in
at said interface) are not directed to the routing
processor. Instead, the decision on how to handle such
data packets is performed locally at said interface. This
will of course further reduce the capacity demand placed
25   upon the routing processor as well as the communication
medium.

Preferably, said selecting means will be continuo-
usly updated with routing information provided by said
routing means, said selecting means thereby receiving
30   information as to which destination addressed that actu-
ally does not required data packets, or header portions
thereof, to be transmitted to the routing processor.

Furthermore, the features defining this embodiment
of the invention may actually be seen as defining a novel
35   invention as such. In other words, the solution of per-
forming local routing decisions at said interface without
involving the routing processor, based upon information

continuously provided and updated by the routing proces-
sor, may, per se, be regarded as an inventive idea.

       Generally, all channels of said multi-channel bit-
stream need not be received and processed by said inter-
5   face, while some channels may simply be bypassed at said
interface. Therefore, said interface will typically
comprise means for determining which channels of said
multi-channel bitstream that are to be received by said
interface and that contain data packets that are to be
10   routed by said apparatus.

       As the invention refers to routing in relation to a
multi-channel bitstream carrying isochronous channels,
the aspect of using the invention in a so-called DTM
(Dynamic synchronous Transfer Mode) network forms a
15   preferred embodiment.

       As understood by those skilled in the art, a "header
portion" according to the invention need not actually
reside at the head end of a data packet, nor is it neces-
sarily the destination address of the data packet that
20   forms the essential part thereof. In fact, the actual
location of a "header portion" according to the invention
will be given by the protocol of interest. Similarly, the
kind and/or amount of information that shall be trans-
mitted to the routing processor according to the inven-
25   tion will depend upon, for example, the type of routing
mechanism used, the type of network, and so on. For
example, in some cases a source address or a channel
identifier (physical or virtual) may be used instead of a
destination address as basis for routing. Consequently,
30   the invention is not limited to a specific kind of header
portion.

       The above mentioned and other aspects, advantageous
and features of the invention will be more fully under-
stood from the accompanying claims and from the following
35   detailed description of exemplifying embodiments thereof.

Brief Description of the Drawings

Exemplifying embodiments of the invention will now
be described with reference to the accompanying drawings,
wherein:

5   Fig. 1 schematically shows an example of the struc-
ture of a bitstream in a circuit switched time division
multiplexed network operating according to a DTM
protocol;

Fig. 2 schematically illustrates transfer of asynch-
10   ronous traffic in one of the isochronous channels carried
by the bitstream shown in Fig. 1;

Fig. 3 schematically shows an exemplifying embodi-
ment of an apparatus according to the invention; and

Fig. 4 schematically shows another exemplifying
15   embodiment of an apparatus according to the invention.

Detailed Description of an Exemplifying Embodiments

An example of the structure of a multi-channel
multi-access bitstream B in a circuit switched time
20   division multiplexed network operating according to a DTM
protocol will now be described with reference to Fig. 1.

As shown in Fig. 1, the bitstream B is divided into
recurrent, essentially fixed sized frames, wherein the
start of each frame is defined by a frame synchronization
25   time slot F. Each frame will have a duration of 125 μs.

Each frame is further divided into a plurality of
fixed sized, typically 64 bit, time slots. When using
said frame length of 125 μs, a time slot size of 64 bits,
and a bit rate of 2Gbps, the total number of time slots
30   within each frame will be approximately 3900.

The time slots are divided into control slots C1,
C2, C3, and C4, and data slots D1, D2, D3, and D4. The
control slots are used for control signaling between the
nodes of the network, whereas the data slots are used for
35   the transfer of payload data. Each node connected to the
bitstream B is typically allocated at least one control
slot, i.e. each node will have write access to at least

one control slot. Furthermore, write access to data slots
are distributed among the nodes connected to the bit-
stream. As an example, a first node (connected to the
bitstream B) will have access to a control slot C1 and a
5   set of data slots D1 within each DTM frame of the bit-
stream, another node (also connected to the bitstream)
will have access to a control slot C2 and a set of data
slots D2 within each DTM frame of the bitstream, and so
on. The set of slots allocated to a node as control
10   slot(s) and/or data slot(s) occupy the same respective
slot positions within each DTM frame of the bitstream.
Hence, in the example, said first node's control slot C1
will occupy the second time slot within each DTM frame of
the bitstream.
15   During network operation, each node may increase or
decrease its access to control slots and/or data slots,
thereby re-distributing the access to control slots
and/or data slots among the nodes. For example, a node
having a low transfer capacity demand may give away its
20   access to data slots to a node having a higher transfer
capacity demand. Furthermore, the slots allocated to a
node need not be consecutive slots, but may reside
anywhere within the frame.
          Also, note that each DTM frame typically begins with
25   said frame synchronization time slot, defining the frame
rate on the bitstream, and ends with one or more guard
band time slots G.
          In Fig. 1 at (c), it is furthermore assumed that
said second node, having access to its control slot C2
30   and its range of data slots D2, has established four
channels CH1, CH2, CH3, and CH4 on the bitstream. As
shown, each channel is allocated a respective set of
slots. In the example, the transfer capacity of channel
CH1 is larger than the transfer capacity of channel 2,
35   since the number of time slots allocated to channel CH1
is larger than the number of time slots allocated to
channel CH2. The time slots allocated to a channel occupy

the same time slot positions within each recurrent DTM
frame of the bitstream.

An example of the transfer of asynchronous traffic
in one of the isochronous channels carried by the bit-
stream B shown in Fig. 1 will now be described with
reference to Fig. 2. In Fig. 2, it is assumed that the
channel CH3 shown in Fig. 1 is established to carry
asynchronous traffic in the form of sequentially trans-
mitted variable size data packets, which for example may
be TCP/IP packets or Ethernet frames. (Note that Fig. 2
only shows the sequence of sequential time slots trans-
mitted within the channel CH3). Since Fig. 1 schemati-
cally indicates that channel CH3 comprises seven time
slots within each DTM frame on bitstream B, the first
seven time slots transmitted in the channel CH3, i.e. the
first seven time slots in Fig. 2, will be transmitted in
one DTM frame, the next seven time slots will be trans-
mitted in the next DTM frame, and so on.

Fig. 2 shows data packets transmitted in channel
CH3. Each data packet is encapsulated according to a pre-
defined encapsulation protocol. It is assumed that the
encapsulation protocol defines that each data packet
shall be divided into 64 bit data blocks (corresponding
to the size of a time slot), that a start_of_packet slot
S is to be added to the start of each data packet, and
that an end_of_packet slot E is to be added to the end of
each data packet, thereby forming encapsulated data
packets P1, P2, and P3. In case of gaps between packets,
the bitstream is provided with so called idle slots,
identifying said gaps as not providing valid data.

An exemplifying embodiment of an apparatus according
to the invention will now be described with reference to
Fig. 3, wherein the apparatus 10 comprises an interface
12, a processor bus 24, and a router processor 26. The
interface 12 provides read/write access to a multi-chan-
nel bitstream, for example of the kind described above
with reference to Figs. 1a-1c. The processor bus 24

provides a shared medium for communication between the
router processor, the interface 26, and other interfaces
(not shown) of the apparatus 10. The routing processor 26
provides routing of data packets received at the inter-
5   faces of the apparatus.

The interface 12 in turn comprises a network medium
access unit 14, a time slot counter 16, an input direct
memory access unit 18, a memory 20, a data packet proces-
sor 22, and an output direct memory access unit 32.

10   In operation, the medium access unit receives a
continuous stream of data bits from the bitstream 5.
Based upon frame synchronization information provided in
the bitstream, the time slot counter 16 of the medium
access unit 14 will count the time slot position
15   currently being received on bitstream 5. This count is
then provided to the input direct memory access 18 that
will designate a memory location of memory 20, whereby
the time slot data received on bitstream 5 is written
into the memory location designated by the input direct
20   memory unit. The input direct memory unit will then see
to that a data packet received in a channel defined on
bitstream 5 is stored at a selected memory location of
memory 20.

Typically, each received data packet is encapsulated
25   according to a predefined protocol and will received as a
set of consecutive sequential 64 bit data blocks. The
number of blocks encapsulating a data packet will depend
on the size of the actual data packet.

As a data packet is being stored in memory 20, the
30   data packet processor 22 will derive a header portion
thereof, said header portion containing at least the
destination address of said data packet, and will then
transmit said header portion to the routing processor 26
via the processor bus 24. Note that, according to the
35   invention, the data packet processor 22 does not transmit
the entire data packet to the routing processor 26, but

only a header portion thereof, thereby decreasing the capacity demand placed upon the internal processor bus.

The router processor typically has access to a routing table 28 and a data packet buffer 30, the latter
5   being used when the operation of the routing processor requires temporary storage of a data packet or a portion thereof at the routing processor.

Having received a data packet header from the data packet processor 22, the router processor will derive the
10   destination address thereof an access the routing table 28 for determining which output interface, port, and channel thereof to use when transmitting the data packet associated with said header. Having determined so, the routing processor will send a message to the data packet
15   processor 22 via the processor bus, instructing said data packet processor 22 on which interface and channel that the associated data packet is to be transmitted via.

Having received said message from the routing pro-cessor 26, the data packet processor 22 will act accor-
20   ding to the instruction provided therein. Typically this will involve one of the following measures: a) reading out the body of the data packet from the memory 20 and transmitting it to another interface (not shown) connec-ted to the processor bus; b) instructing the output
25   direct memory access unit 32 to transmit the data packet into a designated channel on bitstream 5; and c) discar-ding said data packet.

Having performed such measures, the data packet processor 22 will inform the input direct memory access
30   unit 18 that the processing of said data packet is comp-leted and that the input direct memory access unit 32 is free to use the memory location occupied by said data packet for storing of new data packets.

As is understood, the output direct memory access
35   unit 32 will see to that data packets are read from the memory 20 and written into the appropriate channels on bitstream 5 in accordance with instructions received from

the data packet processor 22 and in accordance with the time slot count provided by the counter 14.

Another embodiment of an apparatus according to the invention will now be described with reference to Fig. 4.

5　In the apparatus 11 shown in Fig. 4, the only difference compared to the embodiment shown in Fig. 3 is that, in Fig. 4, the data packet processor 22 is provided with a cache routing table 34. The cache routing table contains a list of destination addresses that the routing proces-

10　sor 26 has previously determined shall be routed only to one or more channels on bitstream 5 or shall not be routed at all, i.e. shall be discarded or bypassed at the interface 12.

Consequently, when a received data packet is being

15　stored in memory 20, the data packet processor will compare the destination address of the header thereof against the destination addresses contained in the cache routing table 34. If a match is found, the header portion of the data packet will not be transmitted to the routing

20　processor 26. Instead, the data packet is discarded, by-passed, or routed to another channel on bitstream 5 based upon the information provided by said cache routing table 34, thereby further reducing the processing load on the routing processor 26 and the transfer capacity demand of

25　the processor bus 24. In such an embodiment, any routing performed by the routing processor 26 may cause the rou-ting table to instruct the data packet processor to update the cache routing table.

Note, that if the channel from which said data

30　packet was received does not terminate at the apparatus 11 but instead/also continuos to one or more other down-stream nodes, the data packet will be "bypassed", i.e. forwarded to downstream nodes in the same channel as it was received.

35　Even though the invention has been described above with reference to exemplifying embodiments thereof, these are not to be considered as limiting the scope of the

12

invention. Consequently, as understood by those skilled in the art, different modifications, combinations and alterations may be made within the scope of the invention, which is defined by the accompanying claims.

5

CLAIMS

1. An apparatus providing routing of asynchronous
traffic in a circuit switched synchronous time division
5   multiplexed network, said apparatus comprising:
        an interface (12) providing access to a multi-
channel bitstream carrying isochronous channels;
        routing means (26) for providing routing of data
packets; and
10   a communication medium (24) interconnecting said
interface and said routing means,
        wherein said interface (12) comprises means (18) for
deriving data packets received in at least one of said
isochronous channels, means (22) for transmitting only
15 header portions of said data packets to said routing
means via said communication medium (24), means (20) for
temporarily storing at least body portions of said data
packets, and means (22, 32) for forwarding said data
packets in accordance with routing instructions received
20 from said routing means.

2. An apparatus as claimed in claim 1, wherein said
interface (12) comprises selecting means (43) for deter-
mining if a header portion of a data packet is to be sent
25 to said routing means (26), and wherein said means (22)
for transmitting only header portions of said data
packets to said routing means (26) are arranged to
control the transmission of header portions according to
decision made by said selecting means.
30

3. An apparatus as claimed in claim 2, wherein said
selecting means (43) comprises a table designating
destination addresses of data packets for which the
header portions thereof are not to be transmitted to said
35 routing means.

4. An apparatus as claimed in claim 2 or 3, wherein said selecting means (43) comprises a table designating destination addresses of data packets that are to be discarded at said interface.

5

5. An apparatus as claimed in claim 2, 3, or 4, wherein said selecting means (43) comprises a table designating destination addresses of data packets that are to be transmitted to one or more of the isochronous

10   channels of said multi-channel bitstream that is accessed by said interface.

6. An apparatus as claimed in claim 2, 3, 4, or 5, wherein said selecting means (43) comprises a cache

15   memory that is continuously updated with routing information provided by said routing means.

7. An apparatus as claimed in any one of the preceding claims, wherein said forwarding of a data packet in

20   accordance with routing instructions received from said routing means (26) comprises at least one measure in the group consisting of: forwarding said data packet to another interface connected to said communication medium (24); forwarding said data packet to said routing

25   processor (26); forwarding said data packet to a channel of said multi-channel bitstream; and discarding said data packet.

8. An apparatus as claimed in any one of the preceding

30   ding claims, wherein said interface (12) comprises means (22) for determining which channels of said multi-channel bitstream that are to be received by said interface (12) and that contain data packets that are to be routed by said apparatus.

35

9. An apparatus as claimed in any one of the preceding claims, wherein said interface (12) comprises means

for bypassing channels of said multi-channel bitstream
that are not to be received by said apparatus.

10. An apparatus as claimed in any one of the prece-
ding claims, wherein said data packets, when transmitted
within said channels, are encapsulated according to a
predefined encapsulation protocol.

11. An apparatus as claimed in any one of the prece-
ding claims, wherein said communication medium (24) is a
shared medium connecting said interface and one or more
other interfaces with said routing means.

12. An apparatus as claimed in any one of the prece-
ding claims, wherein said medium (24) is a communication
bus interconnecting said interface and said routing
means.

13. An apparatus as claimed in any one of the prece-
ding claims, wherein said routing means (26) are arranged
to also perform routing in relation to data packets
received at one or more other interfaces of the appara-
tus.

14. An apparatus as claimed in claim 13, wherein
said communication medium (24) is arranged to
interconnect said one or more other interfaces and said
routing routing means (26).

15. An apparatus as claimed in any one of the prece-
ding claims, wherein said network is operating according
to a Dynamic synchronous Transfer Mode (DTM) protocol.

16. An apparatus as claimed in any one of the prece-
ding claims, wherein said bitstream is a multi—access
bitstream.

Fig. 1

Fig. 2

Fig. 3

Fig. 4

PCT

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : **H04L 12/52, 12/56, H04Q 11/04**	**A3**	(11) International Publication Number: **WO 00/21255**
		(43) International Publication Date: 13 April 2000 (13.04.00)

(21) International Application Number: PCT/SE99/01798

(22) International Filing Date: 7 October 1999 (07.10.99)

(30) Priority Data:
9803417-6   7 October 1998 (07.10.98)   SE

(71) Applicant *(for all designated States except US)*: NET INSIGHT AB [SE/SE]; P.O. Box 42093, S–126 14 Stockholm (SE).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: LINDGREN, Per [SE/SE]; Maria Prästgårdsgata 12, S–118 52 Stockholm (SE). BOHM, Christer [SE/SE]; Varpholmsgränd 32, S–127 46 Skärholmen (SE). OLSSON, Bengt, J. [SE/SE]; Rådjursvägen 303, S–147 34 Tumba (SE).

(74) Agent: AWAPATENT AB; P.O. Box 45086, S–104 30 Stockholm (SE).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(88) Date of publication of the international search report:
13 July 2000 (13.07.00)

(54) Title: APPARATUS FOR ROUTING ASYNCHRONOUS TRAFFIC IN A CIRCUIT SWITCHED NETWORK

(57) Abstract

The present invention refers to an apparatus providing routing of asynchronous traffic in a circuit switched synchronous time division multiplexed network, said apparatus comprising an interface (12) providing access to a multi–channel bitstream carrying isochronous channels; routing means (26) for providing routing of data packets; and a communication medium (24) interconnecting said interface and said routing means. According to the invention, said interface (12) comprises means (18) for deriving data packets received in at least one of said isochronous channels, means (22) for transmitting only header portions of said data packets to said routing means via said communication medium (24), means (20) for temporarily storing at least body portions of said data packets, and means (22, 32) for forwarding said data packets in accordance with routing instructions received from said routing means.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/01798

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04L 12/52, H04L 12/56, H04Q 11/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04L, H04Q, H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9501031 A1 (TELEFONAKTIEBOLAGET LM ERICSSON), 5 January 1995 (05.01.95), page 3, line 17 - page 5, line 25, claims 1-24	1-16
	--	
A	WO 9703526 A2 (NORTHERN TELECOM LIMITED), 30 January 1997 (30.01.97), page 10, line 11 - page 15, line 14, claims 1-25	1-16
	--	
A	WO 9417617 A1 (TELEFONAKTIEBOLAGET LM ERICSSON), 4 August 1994 (04.08.94), page 30, line 22 - page 32, line 10, claims 1-40	1-16
	--	

[X] Further documents are listed in the continuation of Box C.   [X] See patent family annex.

*	Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance	
"E"	erlier document but published on or after the international filing date	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	
"P"	document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
6 April 2000	1 3 -04- 2000
Name and mailing address of the ISA/	Authorized officer
Swedish Patent Office Box 5055, S-102 42 STOCKHOLM	Erik Johannesson/CL
Facsimile No. +46 8 666 02 86	Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0537743 A1 (OY NOKIA AB), 21 April 1993 (21.04.93), see whole document	1-16
	--	
A	Journal of High Speed Networks, Volume 3, 1994, Christer Bohm et al, "The DTM Gigabit Network, Journal of High Speed Networks" page 109 – page 126	1-16
	-- --------	

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
WO	9501031	A1	05/01/95	AU	676926	B	27/03/97
				AU	7088794	A	17/01/95
				BR	9406843	A	16/04/96
				CA	2163342	A	05/01/95
				CN	1126012	A	03/07/96
				EP	0705511	A	10/04/96
				FI	956242	A	22/12/95
				JP	8512179	T	17/12/96
				NO	955275	A	16/02/96
				SE	9302176	A	24/12/94
				US	5506841	A	09/04/96
WO	9703526	A2	30/01/97	CA	2225333	A	30/01/97
				CN	1194073	A	23/09/98
				EP	0838110	A	29/04/98
				US	5841771	A	24/11/98
				US	5862136	A	19/01/99
WO	9417617	A1	04/08/94	AU	693084	B	25/06/98
				AU	5982494	A	15/08/94
				AU	6381798	A	18/06/98
				BR	9406142	A	12/12/95
				CA	2153172	A	04/08/94
				CN	1097535	A	18/01/95
				EP	0681770	A	15/11/95
				FI	953594	A	27/07/95
				JP	8505991	T	25/06/96
				MX	9308193	A	31/01/95
				NO	952980	A	21/09/95
				US	5361257	A	01/11/94
				US	5467347	A	14/11/95
EP	0537743	A1	21/04/93	DE	69216355	D,T	28/05/97
				FI	88840	B,C	31/03/93
				FI	914931	D	00/00/00